



Product Code . EL-EELE-11389

Permeability and Fluidisation Studies Apparatus

Description

Permeability and Fluidisation Studies Apparatus

The rate of flow is indicated by a variable area meter. Pressure drop across the bed can be measured either by a 0.5m length water differential manometer or a 0.5m length Mercury manometer (see recommended accessories), depending on the magnitude. The test section tube and all tubing connections are transparent so that operation can be observed and the presence of air bubbles easily detected. No power connections are required and the whole apparatus can be lifted and transported by one person. Flow from a laboratory tap passes through a constant head tank, which also allows air bubbles to be released, and is controlled by hand with a needle valve. Valves are fitted for isolation of various parts of the circuit, together with air release valves. All metal fittings are corrosion resistant.

Technical Details:-

- Sample tube length: 507mm.
- Sample tube I/D: 38mm.

Flow Meter Range:-

- 0.5m water differential manometer.
- 0.5m Mercury manometer.

-
- 50-800ml/min.

We are leading manufacturers, suppliers of Permeability and Fluidisation Studies Apparatus for Electronics Engineering Lab Equipments. Contact us to get high quality Permeability and Fluidisation Studies Apparatus for Electronics Engineering Lab Equipments for schools, colleges, universities, research labs, laboratories and various industries.

{ "@context": "https://schema.org/", "@type": "Product", "name": "Permeability and Fluidisation Studies Apparatus", "image": "http://www.educational-equipments.com/images/catalog/product/764560334PermeabilityandFluidisationStudiesApparatusWithlogo.jpg", "description": "The rate of flow is indicated by a variable area meter. Pressure drop across the bed can be measured either by a 0.5m length water differential manometer or a 0.5m length Mercury manometer (see recommended accessories), depending on the magnitude. The test section tube and all tubing connections are transparent so that operation can be observed and the presence of air bubbles easily detected. No power connections are required and the whole apparatus can be lifted and transported by one person. Flow from a laboratory tap passes through a constant head tank, which also allows air bubbles to be released, and is controlled by hand with a needle valve. Valves are fitted for isolation of various parts of the circuit, together with air release valves. All metal fittings are corrosion resistant. Technical Details:- • Sample tube length: 507mm. • Sample tube I/D: 38mm. Flow Meter Range:- • 0.5m water differential manometer. • 0.5m Mercury manometer. • 50-800ml/min. We are leading manufacturers, suppliers of Permeability and Fluidisation Studies Apparatus for Electronics Engineering Lab Equipments. Contact us to get high quality Permeability and Fluidisation Studies Apparatus for Electronics Engineering Lab Equipments for schools, colleges, universities, research labs, laboratories and various industries.", "brand": "Educational Lab Equipments", "sku": "5", "gtin8": "5", "gtin13": "5", "gtin14": "5", "mpn": "5", "aggregateRating": { "@type": "AggregateRating", "ratingValue": "5", "bestRating": "5", "worstRating": "0", "ratingCount": "15" } }

Educational Lab Equipments,
#449, HSIIDC, Industrial Area, Saha, Haryana
Direct Contact Details ☎ +91-98173-19615 ✉ sales@educational-equipments.com
🌐 www.educational-equipments.com