



Product Code . EL-CTM-11745

Electro-Hydraulic Trainer

Description

Electro-Hydraulic Trainer

Specification:-

Hydraulic Components

Hydraulic Power pack with following features

Geared pump coupled with induction motor 2HP 220V AC, 50 Hz, and mounted externally over the tank with anti-vibration pads

Having non-return valve, pressure relief valve

Operating pressure 40 bar approx., Flow rate 4-8lpm approx.

Hydraulic Tank capacity 20 liters

Different type of valves

4/3 Double solenoid valve AC operated

4/2 Single solenoid valve AC operated

4/3 Way hand lever valve (Manual)

Flow control valve and Pressure reducing valve (Manual)

Pressure gauges 0-1500Psi - 3nos.

Reduced pressure line at Cylinder 1

Reduced pressure line at Cylinder 2

Pressure gauges (glycerin filled) to measure the pressure at Input Line

Hydraulic Cylinders - 2nos.

Double acting cylinder (Stroke length 100mm & diameter 32mm)

Piston rod: Chrome plated and hardened

Objective:-

Study of different type of hydraulic components

Extension and retraction of double acting hydraulic cylinder in a different way

Control the direction of hydraulic motor using double solenoid valve manually and using micro controller

Cylinder moment using solenoid valve can be done automatically using micro controller

Using hand lever valve and flow control valve

Using single solenoid valve and flow control valve

Hydraulic pipe for fittings:-

Connection type 3/8", Length 600mm - 15nos

Connection type 3/8", Length 1000mm - 2nos

Hydraulic motor:-

Type: Gear motor and Bi-directional

Electronic Controller

220 V AC operated

8051 CPU, Memory 64kB Flash

Line indicator

Single solenoid control switch (Manual and Automatic)

Push buttons for manual control for actuators I, II, & III

USB cable connector

DOL starter start/stop button for Induction motor

Double solenoid control switch (Manual and Automatic)

Power requirement: 220VAC +10%, 50Hz




Weight: -

65Kg Approx. (Main Control Unit)

70Kg Approx. (Hydraulic Power Pack)

Dimensions (mm): 900(L) x 380(B) x 670(H)

```
{ "@context": "https://schema.org/", "@type": "Product", "name": "Electro-Hydraulic Trainer", "image":  
"http://www.educational-equipments.com/images/catalog/product/1416170294Electro-  
HydraulicTrainerWithlogo.jpg", "description": "Hydraulic Components Hydraulic Power pack with  
following features Geared pump coupled with induction motor 2HP 220V AC, 50 Hz, and mounted  
externally over the tank with anti-vibration pads Having non-return valve, pressure relief valve  
Operating pressure 40 bar approx., Flow rate 4-8lpm approx. Hydraulic Tank capacity 20 liters  
Different type of valves 4/3 Double solenoid valve AC operated 4/2 Single solenoid valve AC  
operated 4/3 Way hand lever valve (Manual) Flow control valve and Pressure reducing valve  
(Manual) Pressure gauges 0-1500Psi - 3nos. Reduced pressure line at Cylinder 1 Reduced pressure  
line at Cylinder 2 Pressure gauges (glycerin filled) to measure the pressure at Input Line Hydraulic  
Cylinders - 2nos. Double acting cylinder (Stroke length 100mm & diameter 32mm) Piston rod:  
Chrome plated and hardened Objective:- Study of different type of hydraulic components Extension  
and retraction of double acting hydraulic cylinder in a different way Control the direction of hydraulic  
motor using double solenoid valve manually and using micro controller Cylinder moment using  
solenoid valve can be done automatically using micro controller Using hand lever valve and flow  
control valve Using single solenoid valve and flow control valve", "brand": "Educational Lab  
Equipments", "sku": "5", "gtin8": "5", "gtin13": "5", "gtin14": "5", "mpn": "5", "aggregateRating": {  
"@type": "AggregateRating", "ratingValue": "5", "bestRating": "5", "worstRating": "0", "ratingCount":  
"15" } }
```

Educational Lab Equipments,
#449, HSIIDC, Industrial Area, Saha, Haryana
Direct Contact Details  +91-98173-19615  sales@educational-equipments.com
 www.educational-equipments.com