



Product Code . EL-TWL-11785

RTD Studies in Plug Flow Reactor

Description

RTD Studies in Plug Flow Reactor

Description:-

To predict the exact behavior of a vessel as a Chemicals reactor, RTD or stimulus-response technique is used.

The setup consists of one feed tank through which water is fed to the reactor.

It is a helical coil tube type plug flow reactor made up of Stainless steel pipe.

For understanding the RTD characteristics, a special arrangement to inject tracer into the lower end of reactor, using a syringe is provided

Real reactors do not satisfy the idealized flow patterns, back mix flow or plug flow deviation from ideality can be due to channeling of fluid through the vessel, recycling of fluid within the vessel or due to the presence of stagnant region or pockets of fluid in the vessel.




Reactants enter at the lower end coming out of the top of the coil from where samples are collected for analysis.

To plot RTD curve for Plug Flow Reactor.

The flow rate can be adjusted by operating the needle valve and measured by Rotameter.

The magnetic drive pump is used for circulation of feed.

```
{ "@context": "https://schema.org/", "@type": "Product", "name": "RTD Studies in Plug Flow Reactor",  
"image": "http://www.educational-  
equipments.com/images/catalog/product/254212832RTDStudiesinPlugFlowReactorWithlogo.jpg",  
"description": "To predict the exact behavior of a vessel as a Chemicals reactor, RTD or stimulus-  
response technique is used. The setup consists of one feed tank through which water is fed to the  
reactor. It is a helical coil tube type plug flow reactor made up of Stainless steel pipe. For  
understanding the RTD characteristics, a special arrangement to inject tracer into the lower end of  
reactor, using a syringe is provided Real reactors do not satisfy the idealized flow patterns, back mix  
flow or plug flow deviation from ideality can be due to channeling of fluid through the vessel, recycling  
of fluid within the vessel or due to the presence of stagnant region or pockets of fluid in the vessel.  
Reactants enter at the lower end coming out of the top of the coil from where samples are collected  
for analysis. To plot RTD curve for Plug Flow Reactor. The flow rate can be adjusted by operating the  
needle valve and measured by Rotameter. The magnetic drive pump is used for circulation of feed.",  
"brand": "Educational Lab Equipments", "sku": "5", "gtin8": "5", "gtin13": "5", "gtin14": "5", "mpn": "5",  
"aggregateRating": { "@type": "AggregateRating", "ratingValue": "5", "bestRating": "5", "worstRating":  
"0", "ratingCount": "15" } }
```

Educational Lab Equipments,
#449, HSIIDC, Industrial Area, Saha, Haryana
Direct Contact Details  +91-98173-19615  sales@educational-equipments.com
 www.educational-equipments.com