

Educational Lab Equipments





Product Code . EL-TOMLE-11872

Cariollis Component of Acceleration

Description

Cariollis Component of Acceleration

This set up is designed to study coriollis component of Acceleration of a slider crank Mechanism.

The apparatus uses hydraulic analogy to represent the rotating slider.

It consists of a rotating block with two arms in opposite direction.

A Perspex window on top cover helps to visualize the process. Rotameter is used to measure water flow rate through tubes.

These tubes can be rotated at various speeds by using a swinging field motor, which also acts as a dynamometer to measure torque applied to rotating tubes.

Water is circulated by small monoblaock pump.

Specifications:-

Main Tank with fiberglass lining.

Rotating Arms 9/6 mm dia, 300 mm long.

Motor Swinging field, D.C., 0.5 HP.

Rotameter

Monoblock Pump

Control Panel comprising of:-

Speed Control Unit.

Speed Indicator.

Necessary switches.

Rigid support frame.

Range of Experiment:-

Coriollis Component of Acceleration can be determined at various speeds of rotation and water flow rates.

Service Required:-

A.C. Single Phase .230 V. stabilized supply.

Floor Space:-1.5 m X 1.5 m.

{ "@context": "https://schema.org/", "@type": "Product", "name": "Cariollis Component of Acceleration", "image": "http://www.educational-

equipments.com/images/catalog/product/481281262CoriolisComponentofAccelerationWithlogo.jpg", "description": "This set up is designed to study coriollis component of Acceleration of a slider crank Mechanism. The apparatus uses hydraulic analogy to represent the rotating slider. It consists of a rotating block with two arms in opposite direction. A Perspex window on top cover helps to visualize the process. Rotameter is used to measure water flow rate through tubes. These tubes can be rotated at various speeds by using a swinging field motor, which also acts as a dynamometer to measure torque applied to rotating tubes. Water is circulated by small monoblaock pump. Specifications:- Main Tank with fiberglass lining. Rotating Arms 9/6 mm dia, 300 mm long. Motor Swinging field, D.C., 0.5 HP. Rotameter Monoblock Pump Control Panel comprising of:- Speed Control Unit. Speed Indicator. Necessary switches. Rigid support frame. Range of Experiment:-Coriollis Component of Acceleration can be determined at various speeds of rotation and water flow rates. Service Required:- A.C. Single Phase .230 V. stabilized supply. Floor Space:-1.5 m X 1.5 m.", "brand": "Educational Lab Equipments", "sku": "5", "gtin8": "5", "gtin13": "5", "gtin14": "5", "mpn": "5", "aggregateRating": { "@type": "AggregateRating", "ratingValue": "5", "bestRating": "5", "worstRating": "0", "ratingCount": "15" } }

Educational Lab Equipments,

#449, HSIIDC, Industrial Area, Saha, Haryana

Direct Contact Details 🌭 +91-98173-19615 🖂 sales@educational-equipments.com

www.educational-equipments.com